Environmental Product Declaration Bollywood, Repertoire, and Script



NSF® Certified Environmental Product Declaration www.nsf.org

Program Operator NSF® International **EPD Registration Number** EPD 10838 7/1/2023 Date of Publication 7/1/2028 Date of Validity

This group of woven textiles are extremely durable and have great cleanable attributes.

An EPD should provide current information, and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com.

Knoll Textiles

At KnollTextiles, we advocate for business practices that reduce the use, manufacture, and sale of products that have the potential to cause environmental damage or negatively impact human health and safety. We are dedicated to environmental stewardship and transparency, and as such, we prioritize low-emitting materials, recycled content, natural fibers, and the removal of Chemicals of Concern from our products.

Deepening our commitment to material, production, and operational transparency, we have engaged in Life Cycle Assessments (LCA) for selected products within our line. The LCA is a comprehensive quantitative analysis of the environmental impacts of the entire life cycle of our products. This information will be presented in product-specific Environmental Product Declarations (EPD) that report on the whole-life sustainability impact of operational, embodied, and long-term carbon.



This declaration is an environmental product declaration (EPD) in accordance with ISO 14025 and EN 15804 + A2.

Bollywood, Repertoire, and Script EN 15804 +A2

KnollTextiles

Certified Environmental Product Declaration

According to ISO 14025 and EN 15804 + A2

EPDs rely on Life Cycle Assessment (LCA) to provide information on a number of environmental impacts of products over their life cycle. The EPD owner has the sole ownership, liability and responsibility of the EPD. Exclusions: EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g., Type 1 certifications, health assessments and declarations, environmental impact assessments, etc. Accuracy of Results: EPDs regularly rely on estimations of impacts, and the level of accuracy in estimation of effect differs for any particular product line and reported impact. Comparability: EPDs are not comparative assertions and are either not comparable or have limited comparability when they cover different life cycle stages, are based on different product category rules or are missing relevant environmental impacts. EPDs from different programs may not be comparable. The ranges of the LCIA results are less than 10%.

EPD PROGRAM AND PROGRAM OPERATOR NAME, ADDRESS, LOGO, AND WEBSITE	NSF International, 789 N. Dixboro Rd	Rd, Ann Arbor, MI 48105,www.nsf.org					
PRODUCT CATEGORY RULES (PCR):	EN 15804 +A2						
INDEPENDENT THIRD-PARTY VERIFICATION OF THE DECLARATION AND DATA, ACCORDING TO ISO 14025:2006	EPD Process Certifi	cation	on				
DECLARATION NUMBER	EPD 10838						
DECLARED PRODUCT & DECLARED UNIT	Bollywood, Repertoire, and Script declared unit = 1 m^2 of fabric						
REFERENCE PCR AND VERSION NUMBER	EN 15804:2012+A2:2019: Sustainab the product category of construction p	•	s — Environmental Product Declarati	ons — Core rules for			
DESCRIPTION OF PRODUCT APPLICATION/USE	Knoll products are primarily used in c	ommercial and resident	ial settings.				
PRODUCT RSL DESCRIPTION	Not applicable for this product catego	ry					
MARKETS OF APPLICABILITY	Global						
DATE OF ISSUE	July 1, 2023						
PERIOD OF VALIDITY	5 years						
EPD TYPE	Product Specific						
DATASET VARIABILITY	N/A						
EPD SCOPE	Cradle-to-Gate with Options						
YEAR(S) OF REPORTED PRIMARY DATA	2020						
LCA SOFTWARE & VERSION NUMBER	GaBi 10.6						
LCI DATABASE(S) & VERSION NUMBER	GaBi Sphera database, Service Pack	ack 35					
LCIA METHODOLOGY & VERSION NUMBER	TRACI 2.1; CML 4.1						
PCR REVIEW WAS CONDUCTED BY:	EN15804+A2 Core PCR was develop	oed by the European Co	ommittee for Standardization (CEN)				
This declaration was independently verified in accordance +A2 serves as the core PCR. INTERNAL] EXTERNAL	Tony Favilla, NSF Cer	tification, LLC Afavilla@nsf.org	Paille			
This life cycle assessment was conducted in accordance PCR by:	e with ISO 14044 and the reference	Sustainable Solutions	Corporation				
This life cycle assessment was independently verified in reference PCR by:	accordance with ISO 14044 and the	Jack Geibig, EcoForm	, LLC jgeibig@ecoform.com	Jack Heiling			

Environmental declarations from different programs (ISO 14025) may not be comparable.

Comparison of the environmental performance using EPD information shall consider all relevant information modules over the full life cycle of the products within the building.

This PCR allows EPD comparability only when the same functional requirements between products are ensured and the requirements of EN 15804 are met. It should be noted that different LCA software and background LCI datasets may lead to differences results for upstream or downstream of the life cycle stages declared.

Bollywood, Repertoire, and Script EN 15804 +A2

KnollTextiles



According to ISO 14025 and EN 15804 + A2

General Information

Description of Company/Organization

We at KnollTextiles use modern design to connect people to their work, their lives, their world. Since 1938, we have been recognized internationally for creating workplace and residential furnishings that inspire, evolve, and endure.

Today, our commitment to modern design, our understanding of the nature of work, and our dedication to sustainable design have yielded a unique portfolio of thoughtful products that respond and adapt to changing needs.

Product Description

KnollTextiles High Performance Woven Vinyl Coated Polyester have extreme durability and cleanability features. In addition to that, they have a high resistance to UV. They can be used for wallcovering and upholstery.

Manufacturer Specific EPD

This product-specific EPD was developed based on the cradle-to-grave with options (modules A1-A4 & C1-D) Life Cycle Assessment. The EPD accounts for raw material extraction and processing, transport, product manufacturing, distribution, and end-of-life. Manufacturing data were gathered directly from company personnel. When updated company-specific data were not available, a proxy was used. Product grouping was considered appropriate if the individual product(s) have a similar application and material composition. Any additional contracted facilities names have been withheld due to confidentiality.

Application

Acme, Bollywood, Improv, Petal Pusher, Repertoire, Script textiles are typically used as a direct glue wallcovering, as well as unbacked for wrapped panel or indoor-outdoor upholstery use. Their main function is the same across all products lines, where they differ are their final patterns.

Bollywood, Repertoire, and Script EN 15804 +A2

KnollTextiles

According to ISO 14025 and EN 15804 + A2

Material Composition

The primary product components and/or materials are indicated as a percentage mass to enable the user of the EPD to understand the composition of the product in delivery status. There are no substances in these products listed in the 'Candidate List of Substances of Very High Concern for authorization'. For more information see https://www.knoll.com/shop-textiles.

The average composition of the product(s) is as follows:

Material	Percentage in mass (%)
Vinyl	70.00%
Polyester	30.00%
Total	100.00%
Total Mass	0.86 kg

Technical Data

For the declared product, the following technical data in the delivery status must be provided with reference to the test standard:

	Technical Data								
Composition	Vinyl, Vinyl Coated Polyester								
Weave	Dobby, Vinyl, Jacquard								
Color Index	Various								
Colorfastness Dry	Above ACT minimum Guidelines of Grade 3								
Colorfastness Wet	Above ACT minimum Guidelines of Grade 4.5								
ASTM E-84 Adhered									
ASTM E-84 Unadhered	Meets ACT minimum Guidelines of Class A								
Lightfastness 40 hrs.	Meets ACT minimum Guidelines of Grade 4.5								
ASTM C423 Acoustical	Please see individual product listing at https://www.knoll.com/shop-textiles for specific product rating								
Clean Air	Tested to CDPH/BIFMA guidelines								

Placing on the Market / Application Rules

These products can be used for Upholstery and/or Panel applications.

Bollywood, Repertoire, and Script EN 15804 +A2

Knoll Textiles

Certified Environmental Product Declaration www.nsf.org

According to ISO 14025 and EN 15804 + A2

Methodological Framework

Declared Unit

The declaration refers to the declared unit of 1 m² of Bollywood, Repertoire, and Script as specified in EN 15804 + A2. The declared unit was chosen to be consistent with the unit defined by EPD International PCR: Woven, Knitted or Crocheted Fabrics (of Synthetic Fibres) which was used to inform the EPD created under EN 15804 + A2 and because the use phase is out of scope.

Name	Value	Unit
Declared Unit	1 m2 (one squ	are meter) of fabric
Mass	0.86	kg

System Boundary

This is a cradle-to-gate with options Environmental Product Declaration. The following life cycle phases were considered:

Pr	oduct Sta	ge		truction ss Stage		Use Stage						End of Life Stage*				Benefits and Loads Beyond the System Boundaries
Raw material supply	Transport	Manufacturing	Transport from gate to the site	Construction/ installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction /demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling potential
A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	B6	В7	C1	C2	C3	C4	D
Х	Х	Х	Х	MND	MND	MND	MND	MND	MND	MND	MND	Х	Х	Х	Х	X

Description of the System Boundary Stages Corresponding to the PCR

(X = Included; MND = Module Not Declared)

Reference Service Life

The reference service life of a properly installed textile is not applicable because the use phase is out of scope. The building estimated service life is 75 years.

Allocation

Allocation was determined on the declared unit for primary data, 1 m^2. For secondary data, cut-off methodology was used.

^{*}This includes provision of all materials, products and energy, packaging processing and its transport, as well as waste processing up to the end-of-waste state or disposal of final residues.

Bollywood, Repertoire, and Script EN 15804 +A2

Knoll Textiles

According to ISO 14025 and EN 15804 + A2

Cut-off Criteria

Processes whose total contribution to the final result, with respect to their mass and in relation to all considered impact categories, is less than 1% can be neglected. The sum of the neglected processes may not exceed 5% by mass of the considered impact categories.

For Hazardous Substances the following requirements apply:

- The Life Cycle Inventory (LCI) of hazardous substances will be included, if the inventory is available.
- If the LCI for a hazardous substance is not available, the substance will appear as an input in the LCI of the product, if its mass represents more than 0.1% of the product composition.
- If the LCI of a hazardous substance is approximated by modeling another substance, documentation will be provided.

This EPD is in compliance with the cut-off criteria. No known processes were neglected or excluded. Capital items for the production processes (machine, buildings, etc.) were not taken into consideration.

Data Sources

Primary data were collected for every process in the product system under the control of KnollTextiles. Secondary data from the GaBi Sphera database were utilized. These data were evaluated and have temporal, geographic, and technical coverage appropriate to the scope of the product category rules.

Data Quality

The data sources used are complete and representative of a global system boundary in terms of the geographic and technological coverage and are a recent vintage (i.e., less than ten years old). The data used for primary data are based on direct information sources of the manufacturer. Secondary data sets were used for raw materials extraction and processing, end of life, transportation, and energy production flows. Wherever secondary data is used, the study adopts critically reviewed data for consistency, precision, and reproducibility to limit uncertainty.

Period Under Review

The period under review is the full calendar year of 2020.

Treatment of Biogenic Carbon

The uptake and release of biogenic carbon throughout the product life cycle follows EN 15804 Section Since the product is vinyl and polyester, biogenic carbon is only released through packaging materials.

Comparability and Benchmarking

A comparison or an evaluation of EPD data is only possible if all data sets to be compared were created according to EN 15804 and the building context, respectively the product-specific characteristics of performance, are taken into account. Environmental declarations from different programs may not be comparable. However, variations and deviations are possible. Only EPDs that comply with EN 15804 are comparable.

The LCA results within this EPD are reported in SI units.

According to ISO 14025 and EN 15804 + A2

Additional Environmental Information

Bollywood, Repertoire, and Script


Background data

EN 15804 +A2

For life cycle modeling of the considered products, the GaBi 10.6 Software System for Life Cycle Engineering, developed by Sphera, is used. The GaBi-database contains consistent and documented datasets which are documented in the online GaBi-documentation. To ensure comparability of results in the LCA, the basic data of GaBi database were used for energy, transportation and auxiliary materials.

Manufacturing

There are three basic steps required for fabric production. The first step is yarn production. This happens after the raw materials have been harvested and involves spinning the material into yarn and threads. For most manufacturing sites, this is completed using mechanized spinning wheels. After the raw materials are spun into yarn, the individual threads are joined together to form fabric. This step is called weaving and is done on a machine called a loom. After the fabric has been woven, it is removed from the loom and processed. In this step, the fabric is cleaned and treated with various chemicals and cleaners to remove impurities from the final product. The result of these steps is an all-white fabric. The last, optional, step is the dyeing of the fabric to its final color/pattern.



Bollywood, Repertoire, and Script

According to ISO 14025 and EN 15804 + A2

Packaging

EN 15804 +A2

All packaging is fully recyclable. The packaging material is composed by cardboard, HDPE, LDPE, paper, and tape.

Material	Quantity (% By Weight)	Mass (g/m2)
Cardboard	93.32%	63.30
HDPE	0.34%	0.23
LDPE	6.10%	4.14
Paper	0.13%	0.09
Tape	0.10%	0.07
Total	100%	67.83

Transportation

Transport to Building Site (A4)										
Name	Value	Unit								
Fuel type		Diesel								
Liters of fuel	38	l/100km								
Transport distance	800	km								
Capacity utilization (including empty runs)	90	%								
Gross density of products transported	-	kg/m ³								
Weight of products transported	-	kg								
Volume of products transported	-	m ³								
Capacity utilization volume factor	1.00	-								

Disposal

End of life (C1-C4)									
Name	Value	Unit							
Collected separately	0.22	kg							
Collected as mixed construction waste	0.64	kg							
Reuse	0.00	kg							
Recycling	0.22	kg							
Landfilling	0.64	kg							
Incineration with energy recovery	0.00	kg							
Energy conversion	44%	%							
Material for final deposition	0.86	kg							
Removals of biogenic carbon	0.00	kg							

Re-use Phase

Re-Use, recovery, And/Or Recycling P	otential (D)	
Name	Value	Unit
Net energy benefit from energy recovery from waste treatment declared as exported energy in C3 (R>0.6)	0.00	MJ
Net energy benefit from thermal energy due to treatment of waste declared as exported energy in C4 (R<0.6)	0.00	MJ
Net energy benefit from material flow declared in C3 for energy recovery	0.00	MJ
Process and conversion efficiencies		
Further assumptions for scenario development (e.g. further processing technologies, assumptions on correction factors);		

Knoll Textiles



According to

ISO 14025 and EN 15804 + A2

LCA Results per Declared Unit

EN 15804 +A2

Bollywood, Repertoire, and Script

EN15804 + A2 Impact Assessment												
Parameter	Parameter	Unit	A1	A2	А3	A4	C1	C2	C3	C4	D	
	Total	kg CO2 eq	5.31E+00	7.06E-02	2.55E+00	1.02E-01	0.00E+00	8.17E-03	0.00E+00	5.74E-01	0.00E+00	
	Fossil	kg CO2 eq	5.41E+00	7.06E-02	2.47E+00	1.02E-01	0.00E+00	8.17E-03	0.00E+00	1.36E-01	0.00E+00	
Climate Change	Biogenic	kg CO2 eq	-9.71E-02	0.00E+00	7.11E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.37E-01	0.00E+00	
	Land use and land use change	kg CO2 eq	5.53E-04	0.00E+00	7.06E-05	0.00E+00	0.00E+00	0.00E+00	0.00E+00	7.70E-06	0.00E+00	
Ozone Depletion		kg CFC-11 eq	3.45E-10	1.80E-12	3.02E-13	2.61E-12	0.00E+00	2.08E-13	0.00E+00	4.63E-14	0.00E+00	
Acidification		Mole of H+ eq	1.15E-02	4.59E-04	1.14E-03	6.66E-04	0.00E+00	5.31E-05	0.00E+00	8.51E-04	0.00E+00	
	Freshwater	kg P eq	2.56E-05	1.97E-08	2.58E-06	2.86E-08	0.00E+00	2.28E-09	0.00E+00	2.71E-05	0.00E+00	
Eutrophication	Marine	kg N eq	2.39E-03	1.77E-04	1.50E-03	2.56E-04	0.00E+00	2.04E-05	0.00E+00	4.36E-04	0.00E+00	
	Terrestrial	Mole of N eq	2.54E-02	1.93E-03	5.30E-03	2.80E-03	0.00E+00	2.23E-04	0.00E+00	3.72E-03	0.00E+00	
Photochemical Ozone Formation	Human Health	kg NMVOC eq	8.29E-03	5.20E-04	1.46E-03	7.55E-04	0.00E+00	6.02E-05	0.00E+00	4.79E-04	0.00E+00	
Depletion of	Mineral and metals	kg Sb eq	3.88E-07	0.00E+00	1.48E-07	0.00E+00	0.00E+00	0.00E+00	0.00E+00	8.41E-10	0.00E+00	
Abiotic Resources	Fossil fuels	MJ	1.08E+02	8.87E-01	3.71E+01	1.29E+00	0.00E+00	1.03E-01	0.00E+00	3.30E-01	0.00E+00	
Water Use		m ³ world eq	1.64E+00	0.00E+00	-3.77E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.24E-02	0.00E+00	
Particulate Matter Emissions		Disease incidences	1.22E-07	1.81E-09	1.42E-08	2.63E-09	0.00E+00	2.10E-10	0.00E+00	6.38E-09	0.00E+00	
Ionizing Radiation ¹	Human health	kBq U235 eq.	5.35E-01	1.56E-20	4.57E-03	2.27E-20	0.00E+00	1.81E-21	0.00E+00	4.97E-04	0.00E+00	
Ecotoxicity ²	Freshwater	CTUe	3.42E+01	3.74E+00	4.69E+00	5.43E+00	0.00E+00	4.33E-01	0.00E+00	6.39E+00	0.00E+00	
2	Cancer	CTUh	3.91E-07	1.87E-11	2.96E-10	2.71E-11	0.00E+00	2.16E-12	0.00E+00	7.17E-11	0.00E+00	
Human Toxicity ²	Non-cancer	CTUh	1.78E-07	1.76E-09	6.87E-09	2.56E-09	0.00E+00	2.04E-10	0.00E+00	8.28E-09	0.00E+00	
Land Use Related Imacts ²		Pt	3.12E+01	0.00E+00	2.56E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.30E-02	0.00E+00	

Disclaimer 1 - This impact category deals mainly with the eventual impact of low doze ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure, nor due to radioactive waste disposal in underground facilities, Potential ionizing radiation from the soil, from radon, and from some construction materials is also not measured by this indicator.

Disclaimer 2 - The results of this environmental impact indicator shall be used with case as the uncertainties on these results are high, or as there is limited experienced with the indicator.

Bollywood, Repertoire, and Script EN 15804 +A2

Knoll Textiles

According to

ISO 14025 and EN 15804 + A2

Results shown below were calculated using TRACI 2.1 Methodology.

				TRACI 2	.1 Impact A	ssessment					
Parameter	Parameter	Unit	A 1	A2	A3	A4	C1	C2	C3	C4	D
	Fossil	kg CO ₂ -Eq.	5.31E+00	6.89E-02	2.42E+00	1.00E-01	0.00E+00	7.98E-03	0.00E+00	3.29E-01	0.00E+00
	Biogenic	kg CO ₂ -Eq.	7.80E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
GWP	Land Use and Land Transformation	kg CO ₂ -Eq.	4.85E+00	6.74E-02	2.30E+00	9.79E-02	0.00E+00	7.80E-03	0.00E+00	3.51E-01	0.00E+00
	Total	kg CO ₂ -Eq.	1.02E+01	1.36E-01	4.72E+00	1.98E-01	0.00E+00	1.58E-02	0.00E+00	6.80E-01	0.00E+00
ODP	Depletion potential of the stratospheric ozone layer	kg CFC-11 Eq.	3.41E-10	2.61E-12	4.66E-15	3.79E-12	0.00E+00	3.02E-13	0.00E+00	1.15E-15	0.00E+00
AP Air	Acidification potential for air emissions	kg SO ₂ -Eq.	1.04E-02	4.14E-04	1.99E-03	6.02E-04	0.00E+00	4.79E-05	0.00E+00	2.04E-03	0.00E+00
EP	Eutrophication potential	kg N-Eq.	1.07E-03	2.29E-05	1.32E-03	3.33E-05	0.00E+00	2.66E-06	0.00E+00	7.90E-04	0.00E+00
SP	Smog formation potential	kg O ₃ -Eq.	1.33E-01	1.14E-02	2.94E-02	1.66E-02	0.00E+00	1.32E-03	0.00E+00	7.28E-03	0.00E+00
FFD	Fossil Fuel Depletion	MJ-surplus	1.08E+01	1.22E-01	5.29E+00	1.77E-01	0.00E+00	1.41E-02	0.00E+00	6.65E-02	0.00E+00

^{*}All disposal stages have been considered and only those with non-zero values have been reported

Results shown below were calculated using CML 2001 - April 2013 Methodology.

				CML 4.1	I Impact As	sessment					
Parameter	Parameter	Unit	A1	A2	А3	A4	C1	C2	C3	C4	D
GWP	Global warming potential	kg CO ₂ -Eq.	5.37E+00	6.91E-02	2.45E+00	1.00E-01	0.00E+00	8.00E-03	0.00E+00	3.53E-01	0.00E+00
ODP	Depletion potential of the stratospheric ozone layer	kg CFC-11 Eq.	3.47E-10	2.60E-12	2.67E-13	3.78E-12	0.00E+00	3.01E-13	0.00E+00	6.71E-14	0.00E+00
AP Air	Acidification potential for air emissions	kg SO₂-Eq.	1.02E-02	3.40E-04	9.12E-04	4.94E-04	0.00E+00	3.94E-05	0.00E+00	7.35E-04	0.00E+00
EP	Eutrophication potential	kg(PO ₄) ³ -Eq.	1.16E-03	6.06E-05	5.29E-04	8.80E-05	0.00E+00	7.01E-06	0.00E+00	8.81E-04	0.00E+00
POCP	Formation potential of tropospheric ozone photochemical oxidants	kg ethane-Eq.	1.12E-03	3.97E-05	2.00E-04	5.77E-05	0.00E+00	4.60E-06	0.00E+00	1.66E-04	0.00E+00
ADPE	Abiotic depletion potential for non-fossil resources	kg Sb-Eq.	7.87E-06	2.87E-11	8.63E-07	4.16E-11	0.00E+00	3.32E-12	0.00E+00	1.64E-08	0.00E+00
ADPF	Abiotic depletion potential for fossil resources	MJ	9.08E+01	8.79E-01	3.58E+01	1.28E+00	0.00E+00	1.02E-01	0.00E+00	5.25E-01	0.00E+00

^{*}All disposal stages have been considered and only those with non-zero values have been reported

Bollywood, Repertoire, and Script EN 15804 +A2

Knoll Textiles



According to

ISO 14025 and EN 15804 + A2

Results below contain the resource use throughout the life cycle of the product.

Resource Use											
Parameter	Parameter	Unit	A1	A2	A3	A4	C1	C2	C3	C4	D
SM	Use of secondary material	kg	0.00E+00								
RSF	Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	5.02E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00	5.67E-04	0.00E+00
NRSF	Use of nonrenewable secondary fuels	MJ	0.00E+00								
FW	Use of net fresh water	m ³	4.40E-02	0.00E+00	5.02E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00	5.67E-04	0.00E+00
PERE	Use of renewable primary energy	MJ	1.36E+01	0.00E+00	1.84E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.60E-02	0.00E+00
PERM	Use of renewable primary energy resources used as raw materials	MJ	0.00E+00								
PERT	Total Use of Renewable primary energy	MJ	1.36E+01	0.00E+00	1.84E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.60E-02	0.00E+00
PENRE	Use of Non-renewable Primary Energy	MJ	1.08E+02	8.87E-01	3.72E+01	1.29E+00	0.00E+00	1.03E-01	0.00E+00	3.34E-01	0.00E+00
PENRM	Use of non-renewable primary energy resources used as raw materials	MJ	0.00E+00								
PENRT	Total Use of Non- renewable Primary Energy	MJ	1.08E+02	8.87E-01	3.72E+01	1.29E+00	0.00E+00	1.03E-01	0.00E+00	3.34E-01	0.00E+00

^{*}All disposal stages have been considered and only those with non-zero values have been reported

Results below contain the output flows and wastes throughout the life cycle of the product.

Output Flows and Waste Categories											
Parameter	Parameter	Unit	A1	A2	А3	A4	C1	C2	C3	C4	D
HWD	Hazardous waste disposed	kg	1.27E-04	0.00E+00	2.72E-09	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.24E-11	0.00E+00
NHWD	Non-hazardous waste disposed	kg	4.24E-02	0.00E+00	1.65E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	6.32E-01	0.00E+00
HLRW	High-level radioactive waste	kg or m ³	4.73E-03	0.00E+00	4.75E-05	0.00E+00	0.00E+00	0.00E+00	0.00E+00	6.69E-06	0.00E+00
ILLRW	Intermediate- and low- level radioactive waste	kg or m ³	0.00E+00								
CRU	Components for re-use	kg	0.00E+00								
MR	Materials for recycling	kg	0.00E+00								
MER	Materials for energy recovery	kg	0.00E+00								
EE	Recovered energy exported from system	MJ	0.00E+00								

^{*}All disposal stages have been considered and only those with non-zero values have been reported

Knoll Textiles



According to

ISO 14025 and EN 15804 + A2


Results below contain direct greenhouse gas emissions and removals throughout the life cycle of the product.

Resource Use											
Parameter	Parameter	Unit	A1	A2	A3	A4	C1	C2	C3	C4	D
BCRP	Biogenic Carbon Removal from Product	kg CO ₂	0.00E+00								
ВСЕР	Biogenic Carbon Emissions from Product	kg CO ₂	0.00E+00								
BCRK	Biogenic Carbon Removal from Packaging	kg CO ₂	7.80E-02	0.00E+00							
BCEK	Biogenic Carbon Emissions from Packaging	kg CO₂	0.00E+00	0.00E+00	7.80E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEW	Biogenic Carbon Emissions from Combustion of Waste from Renewable Sources Used in Production Process	kg CO₂	0.00E+00								
CCE	Calcination Carbon Emissions	kg CO ₂	0.00E+00								
CCR	Carbonation Carbon Removal	kg CO ₂	0.00E+00								
CWNR	Carbon Emissions from Combustion of Waste from Non-renewable Sources Used in Production Process	kg CO₂	0.00E+00								

^{*}All disposal stages have been considered and only those with non-zero values have been reported

LCA Interpretation

The raw material production life cycle stages (A1 and A3) dominate the impacts across all impact categories. This is due to the upstream production of materials used in the product, along with electricity use in the manufacturing of the product. Transportation of raw materials and final distribution impacts were low compared to the raw materials themselves and the manufacturing process.



Bollywood, Repertoire, and Script EN 15804 +A2

Knoll Textiles

Certified Environmental Product Declaration www.nsf.org

According to

ISO 14025 and EN 15804 + A2

Additional Environmental Information

Environmental and Health During Manufacturing

There are no known health and safety concerns when manufacturing the fabrics in this group. There are no emissions to indoor air after or during installation.

Environmental and Health During Installation

There is no known harmful emissive potential. No damage to health or impairment is expected under normal use corresponding to the intended use of the product.

Extraordinary Effects

Fire

No danger to the environment can be anticipated.

Water

Contains no known substances that have any impact on water in case of flood.

Mechanical Destruction

No danger to the environment can be anticipated during mechanical destruction.

Delayed Emissions

Global warming potential is calculated using the TRACI 2.1 and CML 4.1 impact assessment methodologies. Delayed emissions are not considered.

Environmental Activities and Certifications

Globally recognized for pioneering modern fabrics using advanced materials and techniques, KnollTextiles is proud to offer a wide selection of sustainably designed products. Dedicated to environmental stewardship and transparency, we strive to meet our customers' needs for sustainability, healthier materials and third-party certification.

Bollywood, Repertoire, and Script EN 15804 +A2

KnollTextiles

According to

ISO 14025 and EN 15804 + A2

Contact Information

Study Commissioner



KnollTextiles
Vanessa Thompson
Sustainability Coordinator
120 West Pumping Station Road
Suite A
Quakertown, PA 18951
vthompso@knoll.com

LCA Practitioner



Sustainable Solutions Corporation 155 Railroad Plaza, Suite 203 Royersford, PA 19468 USA (+1) 610 569-1047 info@sustainablesolutionscorporation.com www.sustainablesolutionscorporation.com

Bollywood, Repertoire, and Script EN 15804 +A2

KnollTextiles

Certified Environmental Product Declaration

According to ISO 14025 and EN 15804 + A2

References

	PCR Part A PCR Part B	EPD International (2017) General Programme Instructions for the International EPD® System. Version 3.0, dated 2017-12-11 EPD International PCR: Woven, Knitted or Crocheted Fabrics (of Synthetic Fibres) Version 1.0, The International EPD System, Published November 2020.
	GaBi 10.6 ISO 14025	thinkstep.one. GaBi Life Cycle Assessment version 10.6 (software). ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.
-	ISO 14040	ISO 14040:2009-11, Environmental management — Life cycle assessment — Principles and framework.
-	ISO 14044	ISO 14044:2006-10, Environmental management — Life cycle assessment — Requirements and guidelines.
-	EN 15804 + A2	EN 15804:2012+A2:2019: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction product
-	NSF 2015	NSF International – National Center for Sustainability Standards, General Program Instructions, 2015.
	ADAAG-1998	Americans with Disabilities Act Accessibility Guidelines
	ANSI A117.1	Accessible and Usable Buildings and Facilities
	CBC, Title 24 ASTM E90	Barrier Free guidelines Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements
	ASTM E90 ASTM E283	Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Curtain Walls, and Doors Under Specified Pressure
	BHMA A156.21	Thresholds
	UL 10(b)	Gasketing Material for Fire Doors
	UL 10(c)	Positive Pressure Gasketing Material for Fire Doors
	Characterization Method	IPCC. 2020. Climate Change 2020. The Physical Science Basis. Cambridge University Press. (http://www.ipcc.ch/report/ar5/wg1/).
-	Characterization Method	Hauschild M.Z., & Wenzel H. Environmental Assessment of Products. Springer, US, Vol. 2, 1998.
-	Characterization Method	Heijungs R., Guinée J.B., Huppes G., Lankreijer R.M., Udo de Haes H.A., Wegener Sleeswijk A. Environmental Life Cycle Assessment of Products: Guide and Backgrounds. CML. Leiden University, Leiden, 1992.
-	Characterization Method	Jenkin M.E., & Hayman G.D. Photochemical ozone creation potentials for oxygenated volatile organic compounds: sensitivity to variations in kinetic and mechanistic parameters. Atmospheric Environment. 1999, 33 (8) pp. 1275-1293.
-	Characterization Method	WMO. 1999. Scientific Assessment of Ozone Depletion: 1998, World Meteorological Organization Global Ozone Research and Monitoring Project - Report No. 44, WMO, Geneva.
-	Characterization Method	Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources using Environmental Chambers- version 1.2, January 2017.
-	Characterization Method	Intertek Clean Air Gold Certification, ISO 17065 accredited