



Nonfood Compounds

Fiske Brothers Refining Co. DBA Lubriplate Lubricants Co.  
1500 Oakdale Avenue  
P.O. Box 8038 Station  
"A"  
Toledo, OH 43605  
United States  
January 09, 2024

May be verified at  
[nsfwhitebook.org](https://nsfwhitebook.org)



Samuel Cole

NSF Nonfood Compounds  
Registration Program

Company No: N03353

## Certificate of Conformity

Fiske Brothers Refining Co. DBA Lubriplate Lubricants Co. has achieved dual Registration and Certification status for LUBRIPLATE SYNXTREME FG-0/220 to the NSF International Registration Guidelines for Proprietary Substances and Nonfood Compounds (2022) and NSF International Certification Policies for ISO21469 - Safety of Machinery - Lubricants with incidental Product Contact - Hygiene Requirements (2023).

### LUBRIPLATE SYNXTREME FG-0/220

Category Code: H1, ISO21469


Certificate No. 149637

**This product has met the requirements of the NSF ISO 21469 certification for lubricants with incidental product contact. The product is intended to be used as a lubricant in the production of food, food processing, cosmetics, pharmaceutical, and animal feeding products and packaging.**

**This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.**

**This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.**

**This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the**



**equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.**

Certification of this product is current when the ISO 21469 Certification Mark appears on the product label reviewed by NSF, and the product name is in the NSF White Book™ ([www.nsfwhitebook.org](http://www.nsfwhitebook.org)).

Listing of nonfood compounds by NSF International is not an endorsement of those compounds or of any performance or efficacy claims made by the manufacturer.